



NOTICE




Miami-Dade County Fire Rescue Department

Effective September 1, 2005, in accordance with NFPA 1: 10.12.1, 10.12.2 and 10.12.3

- **NEW AUTOMATIC GATED ENTRYWAYS** to residential communities or multi-family complexes and commercial properties with keyed automatic entryways may use only a Knox key switch (model 3502) to allow responding emergency personnel access to the property. No other system or model will be permitted.
- **EXISTING AUTOMATIC GATED ENTRYWAYS** to residential communities or multi-family complexes and commercial properties that employ any method of access to emergency personnel other than a functional toggle switch in a Supra Max box will be required to upgrade to a Knox key switch system (model 3502). No other system or model will be permitted.
- **MANUAL GATED ENTRYWAYS** to commercial properties, where padlocks are used and are allowed by code, shall also use a Knox padlock (model 3753) along with the owner's padlock to allow responding emergency personnel access to the property. No other system or model will be permitted.

Knox key switch (model 3502) or padlock (model 3753) can be purchased from the Knox Company at website <http://www.knoxbox.com/store/> or telephone number **(800) 552-5669 extension #1.**

The customer service representative must be told the key switch or padlock being ordered is for use in "Miami-Dade Fire Rescue" jurisdiction (system code #PS-31-291-08-05).




Gated communities, apartment complexes, parking garages, pedestrian gates and industrial receiving areas are just a few applications of the Knox electric override key switch. It also controls emergency power system shutoff and can be ordered with single or dual key options for fire, EMS and law enforcement access.


Features

- Single or dual key switch
- Fire or law enforcement identification labels
- One position, two position or momentary switch
- Face plate and lock cover ensure weather resistant operation.

Electrical Data
 SWITCH: SPDT
 7 A res., 4 A ind., (sea level), 28 VDC
 7 A res., 2.5 A ind., (50,000 ft.), 28 VDC
 7 A res. or ind., 115 VAC, 60 Hz
 U.L. and CSA listed 7 A, 250 VAC
 Temperature tolerance up to +180° F


Con  N.C.
 N.O.

Knox Rapid Entry System
 The Knox Company manufactures a complete line of high security products including Knox Boxes, key vaults, armored cabinets, key switches, padlocks, locking PBC caps, the Knox-Scan infrared heat sensor, and an electronic master key security system. For more information or technical assistance, please call Customer Service at 1-800-552-5669.




**Knox Key Switch
3500 Series**
for Emergency Override

**Single Switch
Model 3502**



**Dual Switch
Model 3503**



Order Specifications

Dimensions: Requires 2 1/4" recessed depth x 2 1/4" diameter
 Switch: SPST, 7 A res., 4 A ind., key nonremovable position
 Mounting: Key switch is designed for recess mounting
 P/N: 3500 Series Knox Key Switch (parts cat. 03)
 Jitter Name: KNOX COMP 16107

© Copyright 2008, Knox Company

KNOX COMPANY

1161 W. Deer Valley Road, Phoenix, Arizona 85027 • 800.552.5669 • (602) 981-2200 • Fax (602) 981-2299 • www.knox.com • info@knox.com



Key Switch



Padlock